


# Melville® Aqua Paver




- Pedestrian - Designed to withstand pedestrian traffic
- Vehicular - Designed to withstand car traffic
- Permeable - Designed to allow runoff to pass through


## Melville® Aqua Paver

	DIMENSIONS (MM)	DIMENSIONS (IN)	CODES	COLOURS	TYPICAL ROW
A	80 x 190 x 380	3 1/8 x 7 1/2 x 15			
B	80 x 380 x 380	3 1/8 x 15 x 15	<b>PRESTIGE COLOURS</b>		
C	80 x 380 x 570	3 1/8 x 15 x 22 7/16	10551036	Range Scandinavia Grey	
			Sold in full cubes only Production location Montréal		
	Weight/unit (avg.)	25 kg	56 lb		
	Unit/surface (avg.)	6.94 unit/m <sup>2</sup>	0.64 unit/ft <sup>2</sup>		
	Area/layer	0.88 m <sup>2</sup>	9.33 ft <sup>2</sup>		
	<b>Area/cube</b>	<b>7.80 m<sup>2</sup></b>	<b>9 Rows</b>	<b>83.97 ft<sup>2</sup></b>	
	Length/row	2.28 lin. m	7.48 lin. ft		
	Length/cube	20.52 lin. m	67.32 lin. ft		
	Weight/cube	1399 kg	3085 lb		

### LAYING PATTERNS



Linear



Modular

### TECHNICAL INFORMATION

Product	Standard	Flexural Strength	Compressive Strength	De-icing salts freeze-thaw durability	Density	Absorption	Dimension Tolerance*
<b>Melville Aqua Paver</b>	CSA A231.2	N/A	μ 50 MPa ≥ 45 MPa	225 g/m <sup>2</sup> after 28 cycles 500 g/m <sup>2</sup> after 49 cycles	N/A	N/A	Length: -1.0 to +2.0 mm Width: -1.0 to +2.0 mm Height: ±3.0 mm

Compaction: Cover vibrating plate with a removable rubber tread (neoprene or polypropylene).

Cover snow removal tools with Teflon or neoprene protectors to minimize the risk of damage from scratches. Laying patterns are for design purposes only. Permacon shall not be responsible for excess or shortage of material.