

SORENO™ SLAB

ENDURACOLOR™

Exclusive to **UNILOCK**



LIGHT GRANITE



TOSCANA BEIGE

VISUAL APPEARANCE

Smooth and elegant in appearance for a sleek and modern look.

FINISH

Flamed-like texture made of fine-grained, natural stone grit.

PRODUCT SPECIFICATIONS



SLAB
16 x 32 x 2"
400 x 800 x 50mm

EDGE DETAILS



ROUNDED EDGE

*Colour selection should be chosen from actual samples.

TECHNICAL INFORMATION

ASTM C 936 Standard Specifications for Solid Concrete Interlocking Paving Units



Conforms to:

- C140 for Absorption 5% avg - 7% max
- Compressive Strength > 7,200 PSI avg.
- C67 for Freeze-thaw Durability
- C418 for Abrasion Durability
- Dimensional Accuracy **+/- 3mm**

Test results available upon request

Meets the U.S. Architectural & Transportation Barrier Compliance Board Slip-Resistance Surfaces Advisory Guidelines

SOLAR REFLECTIVE INDEX (SRI) TESTING DETAILS

| Product | Solar Reflectance | SRI |
|---------------|-------------------|--|
| Light Granite | 0.44 | 50  |
| Toscana Beige | 0.64 | 77  |

TECHNICAL ADVANTAGES

ENDURACOLOR™

Refined surface and long-lasting colour



Factory sealed for integral stain resistance



Ultra-smooth surface texture

LEED INFORMATION

Materials & Resources: LEED V4:

Building Product Disclosure and Optimization

Sourcing of Raw Materials - Sourcing of Raw Materials and Extraction • **1 point**

Sourcing of Raw Materials - Leadership Extraction Practices • **1 point**

Material Ingredient Reporting - Material Ingredient Reporting • **1 point**

Material Ingredient Reporting - Material Ingredient Optimization • **1 point**

Environmental Product Declaration • **1 point**

PRODUCT DATA

| | Unit | SqFt Per | | | | Per Bundle | | Soldier LnFt Per | | | Sailor LnFt per | | | Units Per | | | Lbs Per | | |
|--|-----------|----------|-------|---------|-------|------------|---------|------------------|---------|--------|-----------------|---------|--------|-----------|-------|--------|---------|---------|----------|
| Stones & Bundling | Thickness | Bundle | Layer | Section | Stone | Layers | Section | Unit | Section | Bundle | Unit | Section | Bundle | SqFt | Layer | Bundle | Layer | Section | Bundle |
| Chicago Manufacturing / Stocked in Ayr | | | | | | | | | | | | | | | | | | | |
| 16 x 32" | 2" (50mm) | 64.27 | 3.57 | - | 3.57 | 18 | - | 1.34 | - | 24.04 | 2.67 | - | 48.13 | 0.28 | 1 | 18 | 164.78 | - | 2,965.95 |

Notes: Sold in full bundles only on a refundable skid. **Important: A urethane rubber paver mat must be used to prevent scuffing.** All measurements are nominal. For more information, samples or custom options, please contact your Unilock Territory Manager or call 1-800-UNILOCK.

APPLICATIONS



Pedestrian



Roof Deck



*Wall pairing suggestion- U-CARA® Wall or Lineo™ Dimensional Stone

RECOMMENDED SANDS



Romex: Rompox® ECO-Fine

Pedestrian Applications only

- | Ready mixed and easy to use
- | Resin film free
- | Resistant to ants, weeds, de-icing salts
- | Made from 98% natural, recycled or renewable raw materials
- | Pressure washer safe
- | Ideal for joint widths from 5mm (1/4")

Coverage:

| Colour | 5-6mm Joints |
|---|----------------------|
| Beige, Stone Grey, Anthracite 55 lb bag / 1 kg can | 125 sqft / 55 lb mix |



Alliance Gator G2 MAXX Sand

- | Rain safe after 15 minutes (24hr no rain if concrete overlay)
- | Sets above 32° F/ 0° C - may vary depending on weather, drainage, bedding materials and installation
- | Dust free and haze free
- | Requires only one watering
- | Four colours: Beige, Grey, Black and Ivory

Coverage:

| Colour | Narrow Joints | Wide Joints |
|---------------------------------|---------------|-------------|
| Beige, Grey, Ivory 50 lb bag | 65-85 sqft | 22-42 sqft |
| Black 50 lb bag | 58-76 sqft | 20-38 sqft |

RECOMMENDED SEALER



Alliance Gator Hybrid Low Gloss + Colour Enhancer

- | Water-based
- | Low gloss finish
- | Vibrant Colour Enhancer
- | Rain safe after 24 hours

Coverage:

| Size | Area |
|-------------------------|------------|
| 3.78 L / 1 U.S. gal. | 200 sqft |
| 18.9 L / 5.28 U.S. gal. | 1,000 sqft |

*Please refer to Sands & Sealers on pages 190-202 for more detailed information.

Unsure of bonded vs. unbonded product recommendations? Please contact your Unilock Territory Manager for more information.